



**Mesurflo® 2545 Stainless Steel Automatic Balancing Valves
Order Form**

- 1) A separate sheet is required for each configuration change
- 2) Make a check mark by each option and list quantities by each GPM
- 3) Make as many copies as needed for each order

Inlet / Outlet Connection Size / Flange Type		
Size / Model	ANSI	DIN
2" Flanged (50-75 GPM)		
2-1/2" Flanged (50-120 GPM)		
3" Flanged (50-175 GPM)		
4" Flanged (80-225 GPM)		

Options - (Additional Price Required)	
Extended Pressure/Temperature Ports	
Stainless Steel Tag-Chain (SS TAG-CHAIN)	

NOTE: 50.0-100 GPM ARE IN 1 GPM INCREMENTS. 105-225 ARE IN 5 GPM INCREMENTS*											
GPM	QTY	GPM	QTY	GPM	QTY	GPM	QTY	GPM	QTY	GPM	QTY
50		64		78		92		130		200	
51		65		79		93		135		205	
52		66		80		94		140		210	
53		67		81		95		145		215	
54		68		82		96		150		220	
55		69		83		97		155		225	
56		70		84		98		160			
57		71		85		99		165			
58		72		86		100		170			
59		73		87		105		175			
60		74		88		110		180			
61		75		89		115		185			
62		76		90		120		190			
63		77		91		125		195			

*Additional Flow Rates Available Upon Request