



Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"

GPM: 0.20-125.2 (0.50-5.0 psid)

Type: Manual Balancing Valve Hose Kits

Model: Mesurmeter™

Standard Features:

- Venturi Type with Pressure/Temperature Ports and Memory Stop
- Lever Handle
- Cv's: 1/2" - 0.23, 0.46, 0.87, 1.8, 3.3, 5.4
3/4" - 0.55, 1.1, 2.2, 4.0, 6.7
1" - 2.3, 5.4, 9.2, 20
1-1/4" - 5.5, 9.8, 20, 24
1-1/2" - 14, 19, 44
2" - 13, 34, 56
- Stainless Steel Braided Hose (2)
- Hose Lengths 12", 18", 24" & 36"
- Ball Valve with Pressure/Temperature Port
- Each Complete Hose Kit Banded Together with a White Plastic Tie Wrap

Options:

- Y-Ball Strainer with Pressure/Temperature Port & Blowdown Valve w/ Hose Connector (Replaces Ball Valve with Pressure/Temperature Port)
- Custom Tagging Upon Request
- Stainless Steel Tag-Chain Upon Request
- Reducing Adapters Available
- Custom Hose Lengths Available (Consult Factory)
- **Hays Supplied & Installed Electric Control Valve : 1/2, 3/4, 1"**
 - 1) 2-Wire 24v, Zone Valve, Spring Return, Normally Open or Normally Closed
- **Hays Supplied & Installed Electric Control Valve: 1-1/4, 1-1/2" & 2"**
 - 1) 2-Wire 24v, Ball Valve, Spring Returned, Normally Open or Normally Closed

